

**The Director General
Sri Lanka Standards Institution
No.17, Victoria Place,
Elvitigala Mawatha,
Colombo – 08,
Sri Lanka.**

APPLICATION FOR QUALIFICATION APPROVAL UNDER SLS 1396

I hereby apply for Qualification Approval under SLS 1396 with the Sri Lanka Standards Institution.

1. Name of the organization :
2. Postal address :
3. Telephone No :
4. Email address :
5. Details of contact person :
 - a. Name :
 - b. Designation :
 - c. Telephone no :
 - d. Email address :
6. Product details: (Please provide Base oil data, Prototype data and Oil data separately for each brand. Prototype data shall be submitted on official letterhead of the oil manufacturer or brand owner, signed by an authorized officer. Kindly note that all the information provided, shall be treated strictly confidential and will not be divulged to any other party.)

Brand name	SAE Viscosity grade

7. Declaration by the applicant

In order to ensure conformity of the above mentioned products, with SLS 1396: Specification for gear lubricants (extreme pressure gear oil), we agree to provide required information and pay applicable charges with applicable taxes prior to the grant of qualification approval.

In the event the qualification approval being suspended or cancelled, all relevant advertising material will be withdrawn with immediate effect.

Signature:

Date:

Name:

Designation:

Stamp of the Organization:



INFORMATION TO BE SUBMITTED TO OBTAIN QUALIFICATION APPROVAL

Following shall be submitted either on official letter head of the oil manufacturer or brand owner, signed by an authorized officer giving following particulars:

Full name :
 Designation :
 Official address :
 Contact no. & email :

BASE OIL INFORMATION			
1	Name of the base oil :		
2	API category of the base oil:		
PROTOTYPE INFORMATION			
Name of the laboratory:			
Address:			
Reference to the sample tested:			
Date:			
Requirement			Test result
1	Four ball extreme pressure test	Weld point, kg	
2	Four ball wear test	Wear scar diameter, mm	
3	Kinematic viscosity at 100 °C, cSt		
4	Maximum temperature for viscosity of 150,000 cP, °C		
5	Viscosity Index		
6	Flash point, °C		
7	at 24 °C		
8	Foaming tendency	at 93.5 °C	
9		at 24 °C after test at 93.5 °C	
10	Sulfur, %		
11	Phosphorus, %		
12	Sulfated ash, %		
OIL INFORMATION			
Name of the laboratory:			
Address:			
Reference to the sample tested:			
Date:			
Requirement			Test result
13	Maximum temperature for viscosity of 150,000 cP, °C		
14	Kinematic viscosity at 100 °C, mm ² /s		
15	Four ball extreme pressure test	Weld point, kg	
16	Four ball wear test	Wear scar diameter, mm	
17	Viscosity index		
18	Flash point, 0C		
19	at 24 °C		
20	Foaming characteristics	at 93.5 °C	
21		at 24 °C after test at 93.5 °C	
22	Sulfur, %		
23	Phosphorus, %		
24	Sulfated ash, %		
25	Conformity to Clause 5.4.1		
26	Conformity to stability as per Clause 5.5		
27	Conformity to compatibility as per Clause 5.6		

